

## In the Claims

1. (Currently Amended) An apparatus for driving a liquid crystal display including a plurality of pixels arranged in a matrix, the apparatus comprising:

a gray voltage generator generating a plurality of gray voltages;

a data driver selecting data voltages from the gray voltages corresponding to image data and applying the data voltages to the pixels; and

a signal controller supplying the image data for the data driver, determining ~~whether~~ image types of images ~~image~~ represented by the image data in two adjacent frames during an interval period, ~~is motion image or still image~~ based on the difference in the image data between two adjacent frames ~~frames~~ during a filtering period, and suspending image data modification during a predetermined period ~~predetermined control operation~~ if the image types of images during the interval period ~~is~~ is determined to be a still images ~~image~~.

2. (Currently Amended) The apparatus of claim 1, wherein the image data modification ~~predetermined control operation~~ includes at least one of the image data modifications that include DCC (dynamic capacitance compensation), ACCE (adaptive color contrast enhancement), and ACC (accurate color capture).

3. (Currently Amended) The apparatus of claim 1, wherein the signal controller determines the image types as a motion images ~~image~~ when the number of the pixels having different image data between two adjacent frames or the number of the pixels having the difference in the image data between two adjacent frames larger than a predetermined value is more than a predetermined number.

4. (Currently Amended) The apparatus of claim 1, wherein the signal controller comprises:

a data comparator comparing a present image data with a previous image data for each pixel and generating a first comparison signal for each pixel row, the first comparison signal having pulses generated when the present image data differs from the previous image data or

when the difference between the present image data and the previous image data is larger than a predetermined value;

a first counter counting the number of the pulses contained in each of the first comparison signals and generating a second comparison signal for each frame, the second comparison signal having pulses generated when the number of the counted pulses in the respective first comparison signals is larger than a first predetermined number;

a second counter counting the number of the pulses contained in each of the second comparison signals and generating a third comparison signal for the filtering period ~~each of first periods~~, the third comparison signal having pulses generated when the number of the counted pulses in the respective second comparison signals is larger than a second predetermined number; and

a frame state detector determining that the image types during the interval period ~~image data for respective second periods~~ following the filtering period ~~are first periods~~ represent motion images if the respective number of the pulses contained in the third comparison signals for the first interval period ~~periods~~ is more than a third predetermined number and, that if not, the image data for the second filtering period ~~are periods~~ represent as still images, and outputting an image type selection signal having a first state or a second state based on the determination.

5. (Original) The apparatus of claim 4, wherein the first predetermined number is larger than 30% of the total number of possible pulses in the first comparison signal.

6. (Original) The apparatus of claim 4, wherein the second predetermined number is larger than 30% of the total number of possible pulses in the second comparison signal.

7. (Original) The apparatus of claim 4, wherein the third predetermined number is equal to or larger than one.

8. (Currently Amended) The apparatus of claim 4, wherein a the interval ~~first period~~ includes twenty-five ~~five~~ sequential frames.

9. (Currently Amended) The apparatus of claim 8, wherein a the filtering second period includes ~~twenty~~ five sequential frames.

10. (Currently Amended) The apparatus of claim 9, wherein the signal controller determines image types of images represented during a next filtering period that follows the interval period based on the image types of images represented during the interval period ~~a type of an image for a first period is determined to be the same as the type of the image for a preceding second period.~~

11. (Currently Amended) The apparatus of claim ~~18~~ 4, wherein the image type selection signal maintains either ~~a the~~ first state or ~~a the~~ second state during the interval ~~a second~~ period and the next filtering ~~a following first~~ period, and the first state is one of a high state or a low state.

12. (Original) The apparatus of claim 1, wherein the signal controller further comprises a frame memory storing image data for at least one frame.

13. (Original) A method for driving a liquid crystal display including a plurality of pixels arranged in a matrix, the method comprising:

reading out image data of a previous frame and of a present frame;

comparing the image data of the previous frame with the image data of the present frame for every pixel;

generating a first comparison signal for each pixel row, the first comparison signal including pulses generated when the image data of the previous frame differs from the image data of the present frame or the difference between the image data of the previous frame and the image data of the present frame is larger than a predetermined value;

counting the number of the pulses included in each of the first comparison signals;

generating a second comparison signal for each frame, the second comparison signal including pulses generated when the number of the counted pulses in the respective first comparison signals is larger than the first predetermined number;

counting the number of the pulses included in each of the second comparison signals;

generating a third comparison signal for each of first periods, the third comparison signal including pulses generated when the number of the counted pulses in the respective second comparison signals is larger than a second predetermined number;

determining that image data for respective second periods following the first periods represent motion image when the respective number of the pulses included in the third comparison signals is larger than a third determined number, determining as still image if not; and

suspending predetermined control operation if the image data represent still image.

14. (Original) The method of claim 13, wherein a first period includes five sequential frames.

15. (Original) The method of claim 14, wherein a type of an image for a first period is determined to be the same as the type of the image for a preceding second period.

16. (Original) The method of claim 13, wherein a second period includes twenty five sequential frames.

17. (Original) The method of claim 16, wherein a type of an image for a first period is determined to be the same as the type of the image for a preceding second period.

18. (New) The apparatus of claim 10, wherein the image types of images represented during the interval period are substantially the same as the image types of images represented during the next filtering period.

19. (New) The apparatus of claim 11, wherein the predetermined period has a combined length of the interval period and the filtering period.